

Riser Bond Model 6000DSL

MULTI-FUNCTION TELEPHONE NETWORK ANALYZER



FEATURES/KEY BENEFITS

- **Diagnostic and fault location functions in one instrument** – Integrated testing system enables the technician to diagnose and locate faults in POTS and DSL service with one easy to use, high quality instrument.
- **Diagnostic Test Package**- Identify conditions on the line that can adversely affect POTS and/or DSL service using the following diagnostic tools:
 - Multi-Meter** – Measure AC volts, DC volts, foreign battery, resistance and insulation resistance.
 - Pair Quality Tests** – Measure loop current, noise metallic, power influence and longitudinal balance.
 - Power Spectral Density** – Find signals causing interference on active/inactive DSL lines.
 - Insertion Loss** – Measure voice frequency and wideband signal loss using tones generated by the Model 6000DSL's remote device.
 - Crosstalk Tests** – Measure both NEXT and FEXT Crosstalk, selecting either a single frequency to test or a sweep of voice or wideband frequencies.
- **Fault Location Test Package** - Restore existing service quicker or reclaim unused lines for new service with accurate fault location tools:
 - Time Domain Reflectometer (TDR)** – Accurately locate opens, shorts, water in cable, bad splices and cable damage with the same full-function TDR found in Riser Bond's stand-alone instruments.
 - Resistance Fault Locator (RFL)** – Three test modes. Locate resistance faults on a pair or on a single conductor.
 - Stress TDR** – This exclusive feature enhances the instrument's ability to locate faults due to moisture in the cable.
 - Open/Capacitance Meter** – Measure capacitance to the end of the pair or locate fault caused by an open circuit.
- **Ease-of-Use Features** – The soft-key menu's intuitive left-to-right operation guides the technician through logical testing steps to diagnose and locate faults. Most tests are performed using the same connection to the line.
- **Auto-Test and Fault Analysis Functions** – Press the Auto-Test key to perform a series of basic diagnostic tests. The Fault Analysis function will then suggest the appropriate fault location tool to use to most effectively locate the problem.
- **SUPER-STORE Waveform Data Storage** – Analyze TDR waveforms in a more convenient time or place. The instrument also stores Auto-Test and Power Spectral Density records.
- **WAVE-VIEW Software** – View, manipulate, print and archive TDR waveforms on your computer. Document plant, certify new builds, and store waveforms for later comparisons.
- **Remote Device** – One unassisted technician working at a distance from the exchange can disconnect a customer's service, identify the cable pair, open and close the circuit, and reconnect the customer after desired tests are complete. Use up to three remotes simultaneously to test different sections of a line.
- **Large LCD Display** – Test results and interpretive information are presented in an easy to read format on a screen that is larger than those found on many competitive units.

PRODUCT SPECIFICATIONS

PHYSICAL DIMENSIONS

Main instrument without carrying case & accessories

Width:	9.45 inches (240mm)
Height:	6.30 inches (160mm)
Depth:	2.36 inches (60mm)
Weight:	3 pounds (1.3kg)

Main instrument with carrying case & accessories

Width:	11.0 inches (279mm)
Height:	7.80 inches (198mm)
Depth:	6.5 inches (165mm)
Weight:	6 pounds (2.6kg)

Remote Device

Width:	3.94 inches (100mm)
Height:	8.50 inches (216mm)
Depth:	1.58 inches (40mm)
Weight:	1 pound (0.4kg)

Oscillator/Far End Unit

Width:	1.38 inches (35mm)
Height:	9.06 inches (230mm)
Depth:	0.98 inches (25mm)
Weight:	7.41 ounces (210g)

POWER

Internal:	Rechargeable, 7.2V Nickel metal hydride battery pack
External:	12VAC or VDC, 1250mA power supply
Operating Time:	4.75 hours, continuous without backlight

ENVIRONMENT

Operating temperature:	0°C (+32°F) to +50°C (+122°F)
Storage temperature:	-20°C (-4°F) to +60°C (+140°F)
Humidity:	95% maximum relative humidity, non-condensing IEC 68-2-3
Vibration:	IEC 68-2-6
Shock (Bump):	IEC 68-2-29, 40g, 6ms, 1000 shocks in each axis
Drop:	IEC 68-2-27, 1m free fall, packaged in carry case
Moisture rating:	IP54

DISPLAY

320 x 240 dot-matrix, liquid crystal display (LCD) with CCFL backlighting

MULTI-METER

DC Voltage:	0 to 400V
Resolution:	0.1V
Accuracy:	1% ±0.1V

AC Voltage:	0 to 400V
Resolution:	0.1V
Accuracy:	2% ±0.1V

Foreign Battery:	2 to 400V
Resolution:	0.1V
Accuracy:	1% ±0.1V

Resistance:	0 to 1999.9Ω
Resolution:	0.1Ω
Accuracy:	0.2% ±0.2Ω
2kΩ to 10kΩ	
Resolution:	1Ω
Accuracy:	0.2% ±1Ω

INSULATION RESISTANCE

Voltages:	50V/100V/250V/500V
0Ω to 49.99MΩ	
Resolution:	0.01MΩ
Accuracy:	2% ±0.01MΩ
50MΩ to 99.9MΩ	
Resolution:	0.1MΩ
Accuracy:	4%
100MΩ to 999MΩ	
Resolution:	1MΩ
Accuracy:	10%

OPEN/CAPACITANCE METER

0 to 1000ft (0 to 305m)	
Resolution:	1ft (0.3m)
Accuracy:	2% ±3ft (1m)

1000ft to 10,000ft (305m to 3,050m)	
Resolution:	10ft (3m)
Accuracy:	±3%

10,000ft to 100,000ft (3,050m to 30,500m)	
Resolution:	100ft (30m)
Accuracy:	±5%

100,000ft to 150,000ft (30,500m to 45,700m)	
Resolution:	1000ft (300m)
Accuracy:	±8%

PAIR QUALITY

Loop Current:	0 to 120mA
Resolution:	0.1mA
Accuracy:	5% ±0.2mA

Noise Metallic (POTS):	0 to 50dBmC
Resolution:	1dB
Accuracy:	±2dB

Power Influence (POTS):	40 to 100dBmC
Resolution:	1dB
Accuracy:	±2dB

Longitudinal Balance (POTS):	40 to 62dB
Resolution:	1dB
Accuracy:	±2dB

Insertion Loss:	0 to 60dB
-----------------	-----------

Frequency Range:	50Hz to 2MHz
------------------	--------------

Resolution:	1dB
-------------	-----

Output Level:	0 and -10dBm
---------------	--------------

Crosstalk (NEXT and FEXT):	0dB to -40dB
----------------------------	--------------

Frequency Range:	50Hz to 2MHz
------------------	--------------

Resolution:	1dB
-------------	-----

Output Level:	0 and -10dBm
---------------	--------------

Impedance:	100, 120, 135, 600, 900Ω and TN12
------------	-----------------------------------

POWER SPECTRAL DENSITY

Wideband Dynamic Range:	-20dB/Hz to -140dB/Hz
-------------------------	-----------------------

Frequency Range:	20kHz to 2MHz
------------------	---------------

Resolution:	10kHz
-------------	-------

Impedance:	100Ω, 120Ω and 135Ω
------------	---------------------

TIME DOMAIN REFLECTOMETER (TDR)

Loaded and non-loaded cable

Maximum Ranges:

Live waveform:

63,700 feet (19,400 meters) at 99.0% VOP

38,600 feet (11,700 meters) at 60.0% VOP

Range varies with VOP. Maximum testable cable length varies with pulse width and cable type.

Stored waveform:

11,900ft (3,600.0m) at 99.0% VOP

7,200ft (2,200.0m) at 60.0% VOP

Range varies with VOP.

Horizontal Resolution:

Up to 2,000ft (610m): <0.25ft (0.07m) at 99.0% VOP

<0.07ft (0.02m) at 30.0% VOP

Over 2,000ft (610m) 1ft. (0.3m) at any VOP

Vertical Resolution:

14 bits with 137 dots displayed

Vertical Sensitivity:

Greater than 65dB

Output Signal:

Pulse widths of 2ns, 25ns, 100ns, 500ns, 1.5 μ s, 4.4 μ s and 330 μ s

Output Balance:

Variable, from 80 Ω to 120 Ω

Velocity of Propagation:

Two user-selectable display formats:

VOP (%): Non-loaded cable: 30.0% to 99.0%

Loaded cable: 0.8% to 20.0%

V/2: Non-loaded cable: 147.5 to 486.9ft/ μ s
(45.0 to 148.4m/ μ s)

Loaded cable: 3.9 to 98.4ft/ μ s
(1.2 to 30.0m/ μ s)

Input Protection: 400 VAC or VDC up to 60Hz

Distance Accuracy:

Accuracy will vary with cable VOP and cable type: ± 0.5 ft (0.15m) plus $\pm 0.1\%$ of reading

SOFTWARE NOISE FILTERS

50/60Hz, 4x, 8x, 16x, 32x, 64x, 128x

RESISTANCE FAULT LOCATOR (RFL)

Location Range:

0 to 150kft (0 to 45km)

Resistance fault range:

0 to 50M Ω

Accuracy:

3-Wire Test: $\pm 0.25\%$ of DTS plus $\pm 0.4\Omega$

4-Wire Test: $\pm 0.25\%$ of DTS plus $\pm 0.25\Omega$

Kupfmuller Test: $\pm 1.0\%$ of DTS plus $\pm 1\Omega$

Waveform Storage

All with full vertical resolution: 32 waveforms

RISER BOND REMOTE AND OPTIONAL OSCILLATOR

Remote Device:

Communications for: short pair, open pair, exchange connect, disconnect, send loss/crosstalk signals, set terminations, pair identification tone.

Oscillator/Far End Unit:

Communications for: short pair, open pair, exchange connect, disconnect, pair identification tone.

ACCESSORIES:

Standard: Operator's Manual, 110V or 220V charger, nylon carry/accessory bag, shoulder strap, 2 sets telco connection leads plus ground lead, pair shorting strap, VOP card.

Technological advances allow changes in specifications and/or components. Changes may be made without notification.



Radiodetection (USA) 28 Tower Road, Raymond, Maine 04071, USA
Tel: +1 (207) 655 8525 Toll Free: +1 (877) 247 3797 Fax: +1 (207) 655 8535 rd.sales.us@spx.com www.radiodetection.com

Radiodetection Ltd. (UK) Western Drive, Bristol BS14 0AF, UK
Tel: +44 (0) 117 976 7776 Fax: +44 (0) 117 976 7775 rd.sales.uk@spx.com www.radiodetection.com

© 2013 Radiodetection Ltd. All rights reserved. Radiodetection is a subsidiary of SPX Corporation. SPX, the green ">" and "X" are trademarks of SPX Corporation, Inc. Radiodetection and Riser Bond are trademarks of Radiodetection Ltd. Due to a policy of continued development, we reserve the right to alter or amend any published specification without notice. This document may not be copied, reproduced, transmitted, modified or used, in whole or in part, without the prior written consent of Radiodetection Ltd.