

CLAMPITTER™

cut the cord

Cut the cord

For added safety, more convenience and increased productivity, cut the cord. The CLAMPITTER™ is a self-contained, stand-alone, transmitting inductive coupler.

Three Frequencies

The unit is engineered with 3 highly capable frequencies: 33Khz, 65Khz and 82Khz. These frequencies are commonly available on most locators from a wide range of manufacturers. And, cutting the cord means you don't have to match your output jack to use with a different brand of locator.

Compact & Lightweight

Long trudges in the field feel better when carrying the CLAMPITTER™. This unit is 0.8 pounds and ready for action on its 3 available inductive frequencies. There is no need to worry about hauling that heavy transmitter to the field.

High & Low Power Outputs

Adjustable power settings allow for the just the right amount of signal to be applied. For short runs in congested areas the low power can prevent bleed over. The high power setting will light up the most stubborn and resistive circuits.

Rechargeable Battery

No fumbling for more D-cells to keep your locates rolling. The CLAMPITTER™ can be charged with a simple, standard USB cord (with a whopping 14 hours of continuous use on a full charge!). And there's no messy wall and car chargers falling out of your bag.

Hot Stick Ready

D-ring and 1/4 inch threaded insert for fitting of hotstick and lanyard.



Specifications

Operating Frequencies:	33kHz (32,768Hz), 65kHz (65,536Hz) & 82kHz (82,315Hz)
Output Power Levels:	Low Power / High Power
Power Source:	Rechargeable Li-Ion Battery
Battery Life:	14 Hours (continuous use)
Charging:	Standard USB supply
Operating Temperature:	-4° F to 140° F (-20° C to 60° C)
Inside Diameter:	4.2 Inches (10.67cm)
Dimensions:	5.6" x 10.8" x 1.0" (14.2cm x 27.4cm x 2.4cm)
Weight:	0.8 lbs (0.362kg)
Ingress Protection:	IP 54
Country of Origin:	United States

RYCOM
instruments, inc.

9351 East 59th Street • Raytown, MO 64133-3895, USA
800-851-7347 • 816-353-2100 • FAX 816-353-5050
rycom@rycominstruments.com • www.rycominstruments.com