

# DuraSCOPE™

## WIFI CAMERA REELS

Proudly Designed and Manufactured in North America



Mini Wi-Fi Reel



Mid Wi-Fi Reel



Large Wi-Fi Reel

## Upgrade to DuraSCOPE™!

Hathorn Wi-Fi DuraSCOPE™ reels are designed to work with Wi-Fi PipeSTREAM™ stream/record, using an app for Apple or Android. Stream video inspections directly to your mobile device; record, screen shot, make voice commentary and share video inspections seamlessly. All of these municipal grade Wi-Fi reels are compatible with 18V Milwaukee™ or equivalent batteries for the ultimate in portability. Each reel is fitted with your choice of DuraCAM™ self-leveling or straight view camera heads, all equipped with super bright cool running LEDs, for optimal HD picture quality. Butt welded steel frame construction, stainless steel camera heads, your choice of cable size, and Hathorn's legendary reliability allow you to push further than ever before and remain in the field longer. Hathorn Wi-Fi DuraSCOPE™ camera reels are trusted by plumbers, municipalities, general contractors, home inspectors, petrochemical companies, and mining engineers to deliver a high definition, recordable video inspection every time the camera is used.

### Features

- Wi-Fi PipeSTREAM™ stream/record
- Self-Leveling camera heads standard
- Straight View camera heads available
- On-screen footage counter
- 512hz sonde control and reset
- External 18V battery compatibility
- Industry leading HDPE premium cables



# HATHORN

North America: 1-866-HATHORN  
International: +1-905-604-7040

[www.hathorncorp.com](http://www.hathorncorp.com) • [info@hathorncorp.com](mailto:info@hathorncorp.com)

# DuraSCOPE™

## WI-FI CAMERA REELS

### SPECIFICATIONS

- Compatibility – Wi-Fi PipeSTREAM™ stream/record, an app for all Apple or Android portable devices
- Powered by external Milwaukee™ or comp. 18V batteries.
- DuraCAM™ self-leveling or straight view camera heads with HD picture quality and auto-iris technology
- 1.00" - 8 cool running LEDs - 8k LUX @ 6"
- 1.23" - 12 cool running LEDs - 12k LUX @ 6"
- 1.43" - 16 cool running LEDs - 16k LUX @ 6"
- 1.68" - 20 cool running LEDs - 20k LUX @ 6"
- Choice of premium push-rod with HDPE jacket
- Sonde - 512 Hz High-power
- Operating Temperature – -30C to 60C (-22F to 140F)
- Ingress Protection of Reel & Camera Head – IPx5 to 60PSI

Actual screen shot taken on an iPad from a mini camera in a 3" pipe.



	Catalog#	Camera Head	Self Leveling	Rod Length	Rod Size	Min 90° Elbow	Max. Pipe Well Lit	LBS.	Dimensions
Large	WLR-4168-SL / WLR-4168	1.68"	Avail.	400ft.	1/2"	3"	12"	65lbs.	33"x19"x16"
	WLR-3168-SL / WLR-3168	1.68"	Avail.	300ft.	1/2"	3"	12"	55lbs.	
	WLR-2168-SL / WLR-2168	1.68"	Avail.	200ft.	1/2"	3"	12"	45lbs.	
	WLR-4143-SL / WLR-4143	1.43"	Avail.	400ft.	1/2"	3"	10"	65lbs.	
	WLR-3143-SL / WLR-3143	1.43"	Avail.	300ft.	1/2"	3"	10"	55lbs.	
	WLR-2143-SL / WLR-2143	1.43"	Avail.	200ft.	1/2"	3"	10"	45lbs.	
Mid	WMR-2168-SL / WMR-2168	1.68"	Avail.	200ft.	1/2"	3"	12"	42lbs.	29"x18"x15"
	WMR-2143-SL / WMR-2143	1.43"	Avail.	200ft.	0.400"	3"	10"		
	WMR-2123-SL / WMR-2123	1.23"	Avail.	200ft.	0.400"	2"	6"		
Mini	WMN-2135	1.35"	No	200ft.	3/8"	1.5"	6"	33lbs.	24"x18"x10"
	WMN-2123-SL / WMN-2123	1.23"	Avail.	200ft.	3/8"	2"	6"		
	WMN-2100	1"	No	200ft.	3/8"	1.5"	4"		

\* Camera head skirts are included and always recommended to protect camera heads. Roller skirts are recommended options for pipes larger than 8". Find these accessories and spare parts at our website - [www.hathorncorp.com](http://www.hathorncorp.com)



WiFi App available at:



# HATHORN

North America: 1-866-HATHORN  
 International: +1-905-604-7040  
[www.hathorncorp.com](http://www.hathorncorp.com) • [info@hathorncorp.com](mailto:info@hathorncorp.com)