

Riser Bond Model 1550

METALLIC TIME DOMAIN REFLECTOMETER CABLE FAULT LOCATOR

FEATURES/KEY BENEFITS

- **Low cost** – Increase productivity by equipping more technicians with their own TDRs.
- **Ergonomic design** – Designed to be held comfortably in one hand. Large, well-spaced buttons are easy to use.
- **Small size** – Easy to carry. Compact styling makes it convenient to use in tight spaces.
- **Modular test lead design** – Adaptable to a variety of industries and applications. Modules are available for twisted pair, coaxial cable, and power cable use.
- **Durable, weather-resistant housing** – Suited to indoor and outdoor usage. Rugged plastic case stands up to everyday use.



PRODUCT SPECIFICATIONS

Physical Dimensions:	
Width:	4 inches (100 mm)
Height:	9.8 inches (250 mm)
Depth:	2.2 inches (55 mm)
Weight:	1.3 pounds (600 g)
Power:	Six AA Alkaline batteries
Environment:	
Operating temperature:	-20° C (-4° F) to +55° C (+131° F)
Storage temperature:	-30° C (-22° F) to +70° C (+158° F)
Humidity:	93% relative humidity at 40° C
Display:	128 x 64 dot-matrix, liquid crystal display (LCD) with backlight
Ranges:	33 ft (10 m) 98 ft (30 m) 330 ft (100 m) 980 ft (300 m) 3300 ft (1000 m) 9800 ft (3000 m)
Ingress Protection:	Water resistant to BS2011, Part 2.1 R.IEC 68-2-18, Test Ra
Cursor:	Single, vertical line
Resolution:	1% of range
Gain:	Automatic; varied across screen
Pulse Amplitude:	5V nominal when unterminated
Output Impedance:	25, 50, 75, and 100Ω switchable
Velocity of Propagation:	Adjustable from .20 to .99
Output Sockets:	2 x 4 mm on 19 mm pitch
Output Pulses:	7 nsec to 2000 nsec selected according to range
Distance Accuracy:	± 0.9% of range
Safety:	EC Compliant
Accessories:	
Standard:	Operator's manual, Weatherproof shoulder bag with belt loop, 6 AA batteries.
Optional:	Fused blocking filter test lead for live power cable to 600 VAC, 50 ohm test lead for coax cable and unenergized power cable, 75 ohm test lead for coax cable, 100 ohm test lead for twisted pair cable, BNC to F adaptor.

Technological advances allow changes in specifications and/or components. Changes may be made without notification.



Radiodetection (USA) 28 Tower Road, Raymond, Maine 04071, USA
Tel: +1 (207) 655 8525 Toll Free: +1 (877) 247 3797 Fax: +1 (207) 655 8535 rd.sales.us@spx.com www.radiodetection.com

Radiodetection Ltd. (UK) Western Drive, Bristol BS14 0AF, UK
Tel: +44 (0) 117 976 7776 Fax: +44 (0) 117 976 7775 rd.sales.uk@spx.com www.radiodetection.com

© 2013 Radiodetection Ltd. All rights reserved. Radiodetection is a subsidiary of SPX Corporation. SPX, the green ">" and "X" are trademarks of SPX Corporation, Inc. Radiodetection and Riser Bond are trademarks of Radiodetection Ltd. Due to a policy of continued development, we reserve the right to alter or amend any published specification without notice. This document may not be copied, reproduced, transmitted, modified or used, in whole or in part, without the prior written consent of Radiodetection Ltd.